

TURBO EGR CLEANER



PROPERTIES:

- > Cleans EGR, turbo, collector, throttle valve and combustion chamber
- > eliminates carbon, oil and varnish deposits
- > prevents premature DPF clogging

INSTRUCTIONS: Only for professional use

1. Shake well the product before using. 2. Reach operating temperature. 3. Maintain the engine idling between 1.200 and 2.000 RPM. 4. Open the air intake just behind the air filter and introduce the tube. 5. Spray the product during 3 to 5 seconds and stop. 6. Make sure the spraying improved engine revolution. 7. Repeat step 5 until emptying half part of the product then stop spraying during 5 min. 8. Spray again as step 5 until emptying the entire product. 9. Assemble the air intake and perform a diving test for at least 15 min.

USAGE:

- > Dose for 1 cleaning. Recommended a prior cleaning with CLEANTEKC D425 o D635 o D845
- > Any kind of diesel or gasoline motor vehicle

PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE	PHYSICAL:	spray + propellant gases - non flammable
	COLOUR:	colorless
	SMELL:	characteristic
FLASH POINT:	> 62 °C	
DENSITY (WATER = 1):	0.89	
WATER SOLUBILITY:	insoluble	
VISCOSITY:	Not determined	
EXPLOSION LIMIT:	7.0 LEL: 0.6	

CONTAINERS:

Product code:	11007
Units per box:	12
Content per unit:	300 ml
EAN code:	8436557010117
Material:	tin