

TECHNICAL SHEET

Page 1 of 1

Revision: 06/06/2018 (1)



NANOTEK EXTREME

ENGINE ANTI-FRICTION ¬ ANTI-WEAR

PROPERTIES:

- > Reduces friction and wear
- > Repairs damaged surfaces
- > Reduces oil consumption and fumes
- > Improves the performance of the engine and stabilises the oil
- > Reduces fuel consumption
- > Lubricates turbo and protects the DPF
- > Suitable for any type of engine and compatible with any oil

INSTRUCTIONS:

Dosage for 4 to 6 l of oil. Recommended use after cleaning with 13002 - OIL SYSTEM CLEANER.

USAGE:

> Any kind of motor and motor oil

PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE PHYSICAL: liquid COLOUR: orange

SMELL: characteristic

BOILLING POINT: > 200 °C
DENSITY (WATER = 1): Not determined
WATER SOLUBILITY: < 0.10%

VISCOSITY: Not determined PH: Not determined

CONTAIMER:

Product code: 13004
Units per box: 12
Content per unit: 300 ml
EAN code: 8436557010193
Material: aluminum



OIL SERVICE

VEHIS AUTOMOTIVE BRANDS, S.L.,

Paseo Ferrocarril, nº 335, 4º-1ª, 08860 Castelldefels. Espanha Tel: +34 931 600 104. info@vehisab.com. www.teknum-pro.com

As The information included in this document is a true reflection of our current technical knowledge, and it provides an appropriate description of the product characteristics and lists the applications for which it can be used. The user must ensure, in any case, the application of the product for each specific use. VEHIS AUTOMOTIVE BRANDS, SL., reserves the right to modify the products after the issue date of this document, in order to improve the quality of the same or optimize its performance. The figures of the physical-chemical characteristics are nominal figures. The Safety Data Sheets are available on request.