

**TECHNICAL SHEET** 

Page 1 of 1

Revision: 06/06/2018 (1)



# **CLEANTEK D 635**

# **INJECTION & AIR INTAKE CLEANER**

#### **PROPERTIES:**

- Cleans pump, injectors, valves, combustion chambers, EGR and turbo
- > eliminates carbon, gum and resin deposits
- > lubricates and protects from oxidation and wear
- > Contains PROACTIV 5K e CLEANTEK Detergent Technology

#### **INSTRUCTIONS:**

300 ml for 50 to 70 l of diesel. Pour into tank, idling engine for 15 mins and perform a test drive (high RPM) for 10 km. Best results from 50 km

#### **USAGE:**

- > Any kind of diesel motor vehicle
- > Applicable on injection cleaning machine

### PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE PHYSICAL: liquid COLOUR: light yellow

SMELL: characteristic, heavy

FLASH POINT: 110 °C

DENSITY(WATER = 1): 0.895

WATER SOLUBILITY: insoluble

VISCOSITY: Not determined

EXPLOSION LIMITS (%): EL: 7.0 LEL: 0.6

## **CONTAINERS:**

Product code: 11004
Units per box: 12
Content per unit: 300 ml
EAN code: 8436557010087
Material: aluminium



**DIESEL SERVICE** 

VEHIS AUTOMOTIVE BRANDS, S.L.,

Paseo Ferrocarril, nº 335, 4º-1ª, 08860 Castelldefels. Spain Tel: +34 931 600 104. info@vehisab.com. www.teknum-pro.com

As The information included in this document is a true reflection of our current technical knowledge, and it provides an appropriate description of the product characteristics and lists the applications for which it can be used. The user must ensure, in any case, the application of the product for each specific use. VEHIS AUTOMOTIVE BRANDS, SL., reserves the right to modify the products after the issue date of this document, in order to improve the quality of the same or optimize its performance. The figures of the physical-chemical characteristics are nominal figures. The Safety Data Sheets are available on request