

DPF FLUSHING FLUID



PROPERTIES:

- > Cleans dismantled DPF filter
- > Dissolves and eliminates soot from DPF
- > Cleaning without any risk for aluminium, magnesium, zinc and cadmium parts
- > Suitable for any DPF filter and/or catalytic converter

INSTRUCTIONS: Only for professional use

1. Dismantle DPF and/or catalytic converter and plug one of the holes with adhesive tape. 2. Shake well the product and pour it inside the DPF and/or catalytic converter until fill It up. 3. Wait within 8 and 10 hours depending on the saturation level. 4. Empty the DPF and rinse with hot water. 5. Reassembly the DPF and add DPF Purifier (Ref. 11006) to the tank. 6. Erase all the errors and induce a regeneration cycle. 7. Make a driving test before to deliver the vehicle.

USAGE:

- > Dose for 1 cleaning. Recommended add DPF Purifier after the cleaning

PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE	PHYSICAL:	liquid
	COLOUR:	colorless
	SMELL:	characteristic
FLASH POINT:	> 100 °C	
DENSITY (WATER = 1):	1.0 – 1.1	
WATER SOLUBILITY:	miscible	
VISCOSITY:	Not determined	
PH:	12 - 13	

CONTAINERS:

Product code:	11008
Units per box:	12
Content per unit:	1.000 ml
EAN code:	8436557010148
Material:	PEHD