

TECHNICAL SHEET

Page 1 of 1

Revision: 11/07/2024(1)



UREA ANTICRYSTALLIZING

PROPERTIES:

- > Prevents clogging of the AdBlue® injector and the formation of residue in the SCR filter.
- > Clean the AdBlue® injector and SCR filter.
- > Maintains the correct functioning of the SCR system (injector and filter).
- Protection for 50,000 km or 100 L of Urea.

INSTRUCTIONS: Only for professional use

- 1- With the container lid closed, fill the upper dispenser (25 ml) by pressing the container.
- 2- Open the container lid and pour the contents of the dispenser into the Adblue® cylinder or directly into the vehicle's Adblue® tank.
- 3- Fill the corresponding amount of Adblue® into the tank.
- 4- Start driving normally.

USAGE:

- > Doses of 25 ml per 10L of Adblue®. Doser capacity = 25 ml.
- > 1 container = 10 dose.

PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE PHYSICAL: liquid COLOUR: Bluish

SMELL: Ammonia

 FLASH POINT:
 Non flammable

 DENSITY (WATER = 1):
 1,01 g/ml ± 0,008

 WATER SOLUBILITY:
 Soluble

VISCOSITY: Not determined OIL SOLUBILITY: Not Soluble

CONTAINERS:

Product code: 11011 Units per box: 6 Content per unit: 250 ml

EAN code: 8436557010155

Material: COEX



DIESEL SERVICE

VEHIS AUTOMOTIVE BRANDS, S.L.,

TEKNUM

Paseo Ferrocarril, nº 335, 4º-1ª, 08860 Castelldefels. Spain Tel: +34 931 600 104. info@vehisab.com. www.teknum-pro.com

As The information included in this document is a true reflection of our current technical knowledge, and it provides an appropriate description of the product characteristics and lists the applications for which it can be used. The user must ensure, in any case, the application of the product for each specific use. VEHIS AUTOMOTIVE BRANDS, SL, reserves the right to modify the products after the issue date of this document, in order to improve the quality of the same or optimize its performance. The figures of the physical-chemical characteristics are nominal figures. The Safety Data Sheets are available on request